

1500

INTEGRATED FIRE SUPPRESSION SYSTEM



SUPPRESSION

MOUNTING KIT TOP AND RACK

ASPIRATION DETECTION

DESCRIPTION

The EXXFIRE 1500 can protect up to 2.4m³/84 ft³ or an equivalent of 2 server racks, based on a Class A, B and C type of fire in accordance with NFPA 2001 and UL2127 standards at 24°C/75°F. It contains two Cool Gas Generators each producing 750 Litres or 0.9Kg/1.9Lbs of Nitrogen. The system is manufactured to CE applicable standards.

FEATURES

- Plug and Play
- Easy to install
- Low maintenance
- External mounting kit
- 19" mounting kit
- Air transportable*

*ADR Class 9/UN 3268



THE SYSTEM

- 3 dry contacts with NO/NC relays
- Early smoke detection
- 3 Optical sensors
- Dip switch setting
- Mains powered
- Back-up battery
- LED indicators
- Buzzer



TECHNICAL SPECIFICATIONS

DIMENSIONS MM = 418x443x165 INCH = 16.5x17.1x6.5	WEIGHT KG = 26 LBS = 57	EXTINGUISHING AGENT N2 = Nitrogen	TEMPERATURE RANGE °C = -25 to 65 °F = -13 to 149
GAS MASS (VOLUME) KG = 1.9 L = 1500	PROTECTED VOLUME M ³ = 2.4 FT ³ = 84	OUTPUT PRESSURE BAR = 3-5	LIFETIME GENERATOR YEARS = 10
ADR/UN CLASS UN-USED = 9 UN 3268 CLASS USED = 9 UN 3363 (Exempt)	PROTECTION RATING ENCLOSURE CLASS = IP30 GENERATOR CLASS = IP67	VOLTAGE (MAINS) V = 110/230AC	BATTERY LIFETIME BACK-UP POWER LIFETIME = 4 YRS HRS = 4

CONTACT INFORMATION

EXXFIRE B.V.
 Keyerswey 30
 2201 CW Noordwijk
 The Netherlands

Tel: +31 (0)85 4017 970
 Email: info@exxfire.com
 Website: www.exxfire.com
 CC: 53952464
 VAT: NL.8510.87.425.B01

Local Partner :
Nohmi Bosai (India) Pvt. Ltd.
 Plot 130, 3rd Floor, Sector 44
 Gurgaon, 122001, Haryana, India

Tel: +91 (0)124 4708449
 Email: info@nohmi-india.com
 Website: www.nohmi-bosai-india.com

Performance certified by:



CNPP



VEBONNOVB

